

Material:.....brass
 Claw distance:.....uniform 40 mm. Multiple combinations possible and can be used with all GEKA® plus versions
 Operating pressure:**max. 10 bar**
 Temperature range:approx. -5 °C to +100 °C (depending on the seal ring quality)
 Seal:as standard with GEKA® shaped seal ring 200C, temperature range of approx. -10 °C to +90 °C
 Options:on request GEKA® shaped seal 120C in the qualities NBR form 120, FKM form 200 (200V) as well as dirt filters, available for self-assembly

1

GEKA® hose pieces

Grommet with raised end rib and hose protecting ribbed profile

Hose ID mm	10	13	16	19	25	32	38
Hose size	3/8"	1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"
PU units	10	10	10	10	10	10	10
Covering box units	200	200	180	160	130	90	70
Item no.	08.0100	08.0101	08.0102	08.0103	08.0104	08.0106	08.0107



GEKA® threaded fittings with female thread

NBR flat seal ring on the threaded side

Female thread in mm	11.89	15.39	19.17	24.66	30.93	39.59	45.48
Female thread	G1/4	G3/8	G1/2	G3/4	G1	G1 1/4	G1 1/2
PU units	10	10	10	10	10	10	10
Covering box units	240	230	210	200	170	120	120
Item no.	08.1108	08.1109	08.1110	08.1111	08.1113	08.1114	08.1116



GEKA® threaded fittings with male thread

Male thread in mm	13.16	16.66	20.95	26.44	33.25	41.91	47.80
Male thread	G1/4	G3/8	G1/2	G3/4	G1	G1 1/4	G1 1/2
PU units	10	10	10	10	10	10	10
Covering box units	240	230	220	230	190	170	140
Item no.	08.2119	08.2109	08.2110	08.2111	08.2113	08.2114	08.2116



GEKA® dummy coupling

With bore for chain fastening

PU units	10
Covering box units	230
Item no.	08.3118

