



Hose made of polyester textile covered with POLYURETHANE (PU), with crush-resistant spiral in PA 6, for suction of car exhaust fumes both on the floor and on overhead reels.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE

**



TEMPERATURE RANGE

-40°C +200°C
-40°F +392°F



CHEMICAL RESISTANCE

PU table



CRUSHING RESISTANCE



CAUTION

The coil is not to be coiled when it is still warm.

Ø I.D.	Ø I.D.	Ø O.D.	WALL THICKNESS	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	VACUUM 23°C	TENSILE BREAKING LOAD	SPIRAL PITCH	SPIRAL DIRECTION	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	mm	g/m	mm	m h2o	kg	mm		m	
2	50	63	0.35	-	330	80	5	>130	20	left	30	IN STOCK
	60	75	0.35	-	400	90	3.5	>130	20	left	30	IN STOCK
	75	88	0.35	-	480	100	1.5	>130	20	left	30	IN STOCK
	100	114	0.35	-	700	150	1	>130	20	left	30	IN STOCK
	125	139	0.35	-	850	200	0.8	>130	20	left	30	IN STOCK
	150	164	0.35	-	1200	230	0.6	>130	25	left	30	IN STOCK
	200	216	0.35	-	1600	300	0.5	>130	25	left	20	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.