

915046 RAGNO N 20 BAR



PVC hose with polyester yarn reinforcement and PU adhesive intermediate layer for pressure spraying of insecticides, pesticides, liquids under pressure. *Double reinforcement - see SUPER RAGNO 80 BAR



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-5°C +60°C
23°F +140°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	WORKING PRESSURE 40°C	WORKING PRESSURE 60°C	BURSTING PRESSURE 23°C	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	bar	bar	m	
5/16	8	13	2.5	110	27	20	16	12	60	100	IN STOCK
3/8	10	15	2.5	120	32	20	16	12	60	100	IN STOCK
1/2	13	19	3	180	55	20	16	12	60	100	IN STOCK
5/8	16	23	3.5	300	60	20	16	12	60	100	IN STOCK
3/4	19*	26	3.5	360	70	20	16	12	60	100	IN STOCK
1	25*	34	4.5	510	100	20	16	12	60	50	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.

Double polyester yarn reinforcement, see SUPER RAGNO N 80 BAR CODE 915065 structure.