

# 915143 RAGNO PU CONDUTTIVO



Antiabrasive POLYURETHANE (PU) and thermoplastic rubber compound hose with polyester yarn reinforcement, used on machines with ATEX regulation, for pneumatic tools in general, airbrushes, paint sprayers.



SMOOTH SURFACES

\*\*\*\*\*



FLEXIBILITY

\*\*\*\*\*



ABRASION RESISTANCE

\*\*\*



TEMPERATURE RANGE

-15°C +60°C  
5°F +140°F



CHEMICAL RESISTANCE

PU table



CRUSHING RESISTANCE

\*\*\*



CONDUCTIVE

According to CEI EN 61340-2-3 Surface resistance  $\leq 104 \text{ Ohm}$  VALUE SUBJECT TO VARIANCE

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	WORKING PRESSURE 40°C	WORKING PRESSURE 60°C	BURSTING PRESSURE 23°C	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	bar	bar	m	
1/4	6	10	2	70	20	20	17	15	60	100	ON DEMAND
5/16	8	12	2	85	22	20	17	15	60	60	ON DEMAND
3/8	10	15	2.5	130	38	20	17	15	60	50	ON DEMAND
3/8	10	19	4.5	240	25	20	17	15	60	30	ON DEMAND
1/2	13	19	3	195	65	20	17	15	60	30	ON DEMAND
5/8	16	23	3.5	250	60	20	17	15	60	25	ON DEMAND

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.